

DOC. NO.	REVISION	ISSUE	DATE
QF/RD/05	01	00	16-09-2019



TEMPORARY HORIZONTAL ANCHORAGE LINE Ref. No. Horizon BLU3000 (BC)



CE 0598

TESTED AS PER EN 795:2012 TYPE B+C

DESIGN

- Consists of 30 mm polyester webbing lifeline
- Equipped with ratchet tensioner to tighten the line
- Two auto locking karabiner provided for attachment to anchor points
- Suitable for use by two personnel simultaneously
- Two Cross Arm Straps provided for connection on Anchorage ends

WEIGHT

3450 gm \pm 50 gm

WEBBING

Material	:	Polyester
Width	:	30 \pm 1 mm
Minimum Breaking Strength	:	25 kN

CROSS ARM STRAP

Material	:	Polyester
Width	:	44 \pm 1 mm
Minimum Breaking Strength	:	15 kN

KARABINERS (Two auto locking karabiner , tested as per EN 362:2004)

Material	:	Carbon Steel \varnothing 11 mm
Plating	:	Zinc plated for better finish & corrosion protection
Finish	:	Deburred & Polished

RATCHET TENSIONER

- Made up of Carbon steel
- Capable of tensioning the line by rotary motion
- Spring loaded locking & unlocking mechanism
- Galvanized with yellow passivation

VITAL TEST COMPLIANCE

Static Strength	:	300 Kg for 3 Minutes
Dynamic Performance	:	1.5 M free fall with mass of 100kg