

B806

STYLE AND COMFORT: EASILY ADOPTED PROTECTION

PRESCRIPTION
FRAME
★ EXCELLENCE



Size S



Ref. B806S

Size L



Ref. B806L



S : 20 g
L : 22 g

SUPPLIED WITH

Hard case,
microfibre cloth



FRAME

• Grilamid

LENS MATERIAL AVAILABLE

• CR39
• Polycarbonate

+ UPPER, LOWER AND SIDE PROTECTION

+ ADJUSTABLE NON-SLIP PADS

bolle
SAFETY

B806

STYLE AND COMFORT: EASILY ADOPTED PROTECTION

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
B806 Grilamid/Smoke	S - Tinted side shields	B806S	52/17	EN166 F CE	140 mm
	L - Tinted side shields	B806L	54/17	EN166 F CE	140 mm

LENS MARKING

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.


CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s
CE European standard  Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power +10/-10.

Maximum cylinder compared with sphere : +/-6.

CORRECTED BASE:

Corrected base : 4

PACKAGING AND EAN13 CODE		
	B806S	B806L
Per piece	3660740000332	3660740000325

CHARACTERISTICS	
LENS MATERIALS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Degressive
FRAME MATERIAL	Grilamid / Smoke
STRAP	Non applicable
FOAM	Non applicable



26/02/2019

Europe Bollé Safety
34 rue de la soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : uk@bollebrands.com

bolle
SAFETY