

# XTRA

## LARGE AND UNIVERSAL MODEL

PRESCRIPTION  
FRAME

★ EXCELLENCE



XTRABKL



24 g

#### SUPPLIED WITH

Hard case,  
microfibre cloth

#### FRAME

• TR90  
• PC temples

#### LENS MATERIAL AVAILABLE

• CR39  
• Polycarbonate



- + BUILT-IN SIDE SHIELDS
- + PIVOTING TEMPLES
- + UPPER PROTECTION
- + MAXIMUM COVERING

**bolle**  
SAFETY

# XTRA

## LARGE AND UNIVERSAL MODEL

MODEL	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
XTRA	XTRABKL	58/12	EN166 F C€	120 mm

### LENS MARKING

#### Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

#### CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

### STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +5,5/-8

Maximum cylinder compared with sphere : +/-5

### CORRECTED BASE:

Corrected base : 6

### FRAME MARKING

**EN 166** : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

€ European standard ☞ Manufacturer name

**Bollé safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING** : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE** : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE** : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE	
	XTRABKL
Per piece	3660740009205

CHARACTERISTICS	
LENS MATERIALS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Degressive
FRAME MATERIALS	TR90/PC



Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : uk@bollebrands.com

18/03/2019

**bolle**  
SAFETY