

DOC. NO.	REVISION	ISSUE	DATE
QF/RD/05	03	01	30-12-22

## NO SPARK ANTISTATIC E.A LANYARD PN 328(AS)



CERTIFIED TO EN 355:2002, IS 3521 (PART-2):2021, ATEX 2014/34/EU (EN ISO 80079-36:2016 AND EN ISO 80079-37:2016) LANYARD WEBBING SURFACE RESISTANCE TESTED AS PER: EN 1149-1:2006 AND EN 1149-5:2008

1	PHYSICAL PARAMETERS	GENERAL		<ul style="list-style-type: none"> <li>• Single Leg Fall Arrest Lanyard for safe working at height.</li> <li>• Webbing prevents the risk of an electrostatic discharge igniting the explosive atmosphere.</li> <li>• Anti-Static fall protection system.</li> <li>• Comes with 44mm wide Antistatic polyester webbing.</li> <li>• Equipped with Aluminum Quarter Turn Locking Karabiner (PN 117), Energy Absorber (PN 300(AS)) at one end and Aluminum Scaffold Hook (PN 136) at the other end.</li> </ul>
			WEIGHT	980 gm (2.0 m)
2	TEXTILE COMPONENTS	WEBBING	MATERIAL	Antistatic Polyester
			WIDTH	44 mm $\pm$ 1 mm
			BREAKING STRENGTH	25 kN (Min.)
		STITCHING THREAD	MATERIAL	High-tenacity Polyester
3	METALLIC ASSEMBLY	ALUMINIUM QUARTER TURN LOCKING KARABINER (PN 117)	MATERIAL	High Strength Aluminum Alloy
			BREAKING STRENGTH	23 kN (Min.)
			FINISH	Natural silver/ Colored, anodized
		ALUMINUM SCAFFOLD HOOK (PN 136)	MATERIAL	High Strength Aluminium Alloy
			BREAKING STRENGTH	22 kN (Min.)
			FINISH	Natural silver/ Coloured Anodized

4	VITAL TEST COMPLIANCE	STATIC PRELOADING TEST	AS PER EN 355:2002 AND IS 3521 (PART-2):2021	When tested for static pre-loading, the permanent extension caused by activation of the energy absorber after pre-loading with 2kN is not greater than 50mm(As per EN 355:2002)/40mm(As per IS 3521(Part2):2021.
		STATIC STRENGTH TEST	AS PER EN 355:2002 AND IS 3521 (PART-2):2021	Fully developed E.A sustains a force of 15 kN for 3 minutes without separating, tearing, or rupture of the lanyard or any element connected to it.
		DYNAMIC PERFORMANCE TEST	AS PER EN 355:2002 AND IS 3521 (PART-2):2021	Maximum braking force does not exceed 6 kN in the line when tested on giving free fall of 4 meters to a rigid test mass of 100 kg after raising the mass to its maximum height.