

DOC. NO.	REVISION	ISSUE	DATE
QF/RD/05	01	00	11-07-2024



**RETRACTABLE FALL ARREST  
SYNTHETIC ROPE BLOCK**  
Ref. No. ALGS 12 TO 20



CONFORMS TO EN 360:2002



**PHYSICAL PARAMETERS**

Robust and durable aluminum casing duly powder coated.  
Has anchorage eye at anchorage end.  
Swivel steel snap hook with load indicator our ref. (PN 162) at attachment end.  
Galvanized steel wire rope (option of having S.S. wire rope available)

**LENGTH**

ALGS 12	:	12 Meters
ALGS 15	:	15 Meters
ALGS 18	:	18 Meters
ALGS 20	:	20 Meters

**CABLE**

Material	:	Galvanized steel wire rope Ø4.5mm.
Minimum Breaking Strength	:	15 kN or 1,530 kgf (Min.)

**WEIGHT**

ALGS 12	:	6.86 kgs. ± 0.05 kgs.
ALGS 15	:	7.10 kgs. ± 0.05 kgs.
ALGS 18	:	7.14 kgs. ± 0.05 kgs.
ALGS 20	:	7.50 kgs. ± 0.05 kgs.

**VITAL TEST COMPLIANCE**

Static Strength	:	13 kN or 1,325 kgf for 3 Minutes
Dynamic Performance	:	140 kg mass free fall of 600 mm with the breaking force of less than 6 kN and arrest distance less than 2 mts.

**TECHNICAL DATA SHEET**