

DOC. NO.	REVISION	ISSUE	DATE
QF/RD/05	03	01	13-12-22



CROSS ARM STRAP PN 808



CERTIFIED TO EN 566:2017 AND IS 3521(PART-7):2021 TYPE B

1	PHYSICAL PARAMETERS	GENERAL		<ul style="list-style-type: none"> Made up of 44 mm polyester red webbing with sewn loop terminations on both sides using black thread. Available in length of 0.5m or as requested.
			WEIGHT	120 gm ± 10 gm
2	TEXTILE COMPONENT	WEBBING	MATERIAL	Polyester
			WIDTH	44 mm ± 1 mm
			BREAKING STRENGTH	25 kN (Min.)
		STITCHING THREAD	MATERIAL	High Tenacity Polyester
3	VITAL TEST COMPLIANCE	STATIC STRENGTH TEST	AS PER EN 566:2017	When tested for tensile strength, the tensile strength shall be at least 22kN.
			AS PER IS 3521(PART-7):2021 TYPE B	12 kN sustained for a period of not less than 3 min.
		DYNAMIC STRENGTH AND INTEGRITY TEST	AS PER IS 3521(PART-7):2021 TYPE B	When tested dynamically with a rigid steel mass of 100 kg, the test mass shall be arrested and the drop mass shall remain suspended for 3 min after the drop test.